

ChemProof IWC L

Liquid Form Integral waterproofing Compound for Concrete, Mortar and Plaster

Description:- ChemProof IWC L is a liquid form integral waterproofing compound which is used for waterproofing of concrete, mortar and plaster used in RCC, columns, beams, basements, roof slabs and screeds, water tank, water retaining structure, external plastering, bathrooms and balconies, sumps and drains reacts with the constituents of sand : cement mix to block capillaries and pores in concrete. Its increase concrete workability and consistency for smooth working.

Characteristic Parameters:-

It conforms to specification prescribed in IS 9103 & IS: 2645-2003.

Features/Advantages

- ❖ Liquid admixture: Instant and complete dispersion throughout the mix.
- ❖ Uniform waterproofing throughout concrete matrix.
- ❖ Improved workability and consistency of concrete.
- ❖ Improves compaction of concrete and mortar, even where harsh sands or aggregates are used.

Applications

Mortar: ChemProof IWC L is ideal for use with all sand/cement mortars where it is required to reduce Permeability to a minimum.

Concrete: ChemProof IWC L is recommended for all general mass Concrete work where due to harsh Aggregates, difficulty of Compaction or mix control, the risk of porosity and permeability must be minimized.

E.g. Basements, bund walls, tanks, Balcony, floor and roof Slabs.

Packing: - 1,5,10, 20 and 50 Liter.

Shelf-Life and Storage Condition: - Shelf life is 12 months from the date of manufacturing if stored properly in undamaged and unopened original sealed drum. Keep in dry and cool place & temperature should be +10°C to + 30°C.